

# THREADED ACCESSORIES



## STANDARD ROD COUPLING

**FIG. 100**

**Function:** Designed to provide a means of connecting two lengths of threaded rod with equal diameters.

**Material:** Carbon steel (Type 304 or 316 Stainless Steel upon request)

**Finish:** Plain or electro-galvanized

**Ordering:** Specify figure number, rod size, material, and finish.

Rod Size	Length		Hex Width		Max. Rec. Load		Wt. Each	
					lbs.	kN	lbs.	kg
1/4	7/8	(22.23)	3/8	(9.53)	240	(1.07)	.06	(0.03)
3/8	1 3/4	(44.45)	5/8	(15.88)	730	(3.25)	.11	(0.05)
1/2	1 3/4	(44.45)	1 1/16	(17.46)	1350	(6.01)	.11	(0.05)
5/8	2 1/8	(53.98)	1 3/16	(20.64)	2160	(9.61)	.17	(0.08)
3/4	2 1/4	(31.75)	1	(25.40)	3230	(14.37)	.28	(0.13)
7/8	2 1/2	(63.50)	1 1/4	(31.75)	4480	(19.93)	.56	(0.25)
1	2 3/4	(69.85)	1 3/8	(34.93)	5900	(26.24)	.72	(0.33)

